Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

# Data Sheet
# Fujitsu ESPRIMO P2560 Desktop PC

## Your immediately available Office PC

The ESPRIMO P2560 is designed for price-conscious customers and is equipped with state-of-the-art standard Intel® technology. This system meets every office requirement - especially those typical for small and medium-sized businesses. The ESPRIMO P2560 is available from your dealer at all times and is thus an ideal choice once the decision to purchase has been taken.

**Attractive price**
PC for the day-to-day challenges of office life
- Proven Intel® technology

**Designed and engineered in Germany**
Outstanding quality and stable functions based on German production standards
- The development, production and function tests are all under one roof in Germany

**Immediate availability**
Short waiting times once purchase decision has been taken.
- Preferred versions available on-site

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

# Components

| | |
|---|---|
| **Processor** | Intel® Core™2 Quad processor Q9550 (4 Cores / 4 Threads, 2.83 GHz, 12 MB, 1333 MHz) |
| | Intel® Core™2 Quad processor Q9505 (4 Cores / 4 Threads, 2.83 GHz, 6 MB, 1333 MHz) |
| | Intel® Core™2 Quad processor Q8300 (4 Cores / 4 Threads, 2.5 GHz, 4 MB, 1333 MHz) |
| | Intel® Core™2 Duo processor E8600 (2 Cores / 2 Threads, 3.33 GHz, 6 MB, 1333 MHz) |
| | Intel® Core™2 Duo processor E8500 (2 Cores / 2 Threads, 3.16 GHz, 6 MB, 1333 MHz) |
| | Intel® Core™2 Duo processor E8400 (2 Cores / 2 Threads, 3.0 GHz, 6 MB, 1333 MHz) |
| | Intel® Core™2 Duo processor E7600 (2 Cores / 2 Threads, 3.06 GHz, 3 MB, 1066 MHz) |
| | Intel® Core™2 Duo processor E7500 (2 Cores / 2 Threads, 2.93 GHz, 3 MB, 1066 MHz) |
| | Intel® Pentium® processor E6600 (2 Cores / 2 Threads, 3.06 GHz, 2 MB, 1066 MHz) |
| | Intel® Pentium® processor E5800 (2 Cores / 2 Threads, 3.2 GHz, 2 MB, 800 MHz) |
| | Intel® Celeron® processor E3400 (2 Cores / 2 Threads, 2.6 GHz, 1 MB, 800 MHz) |
| | Intel® Celeron® processor 450 (1 Core / 1 Threads, 2.2 GHz, 512 KB, 800 MHz) |
| **Operating system** | |
| **Operating system** | Genuine Windows® 7 Starter (EM) 32-bit<br>Genuine Windows® 7 Home Basic (EM) 32-bit<br>Genuine Windows® 7 Home Premium 64-bit<br>Genuine Windows® 7 Professional 32-bit<br>Genuine Windows® 7 Professional 64-bit |
| **Operating system compatible** | openSUSE Linux<br>Genuine Windows Vista®<br>Genuine Windows® XP |
| **Operating system notes** | Buy Microsoft® Office 2010 to use the full-featured Office software on this PC.<br>Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com |
| **Memory modules** | 1 GB (1 module(s) 1 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM |
| | 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM |
| | 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1066 MHz, PC3-8500, DIMM |
| **Hard disk drives (internal)** | SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T. |
| | SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T. |
| **Graphics add on cards (optional)** | NVIDIA® GeForce® 405 display port full height |
| | DVI Extension Adapter |
| | DVI-D + DisplayPort Extension Adapter |
| | ATI Radeon® HD 5450, 512 MB |
| **Drives (optional)** | DVD-ROM |
| | DVD Super Multi |
| | MultiCard Reader 20in1, USB 2.0, 3.5-Inch |
| **Interface add on cards/components (optional)** | |
| | WLAN III, 802.11g/Draft-n (Windows only) |
| | USB 3.0 PCIe x1 |
| | Parallel Interface |
| | Modem adapter kit (EU) |
| | Modem 56k incl. RJ11 modem cable |
| | Gigabit Ethernet PCIe x1 |
| | FireWire PCI-Card IEEE1394 |
| | Dual serial card PCI |

| | |
|---|---|
| **Base unit** | ESPRIMO P2560 |
| **Mainboard** | |
| Mainboard type | D3041 |
| Formfactor | reduced ATX |
| Chipset | Intel® G41 |
| Processor socket | LGA 775 |
| Processor quantity maximum | 1 |
| System bus (FSB / HT / QPI) | up to 1333 MHz |
| Memory slots | 2 DIMM (DDR3) |
| Supported capacity RAM (max.) | 8 GB |
| Memory frequency | 1066 MHz |
| Memory notes | For combinations of 32-bit operating systems with 3 GB of memory or above the accessible memory may be reduced to 3 GB or less (depending on system configuration).<br>Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same |
| LAN | 10/100/1000 MBit/s Realtek RTL8111DL |
| BIOS version | Phoenix 6.0 |
| BIOS features | BIOS based on Phoenix SecureCore<br>Recovery BIOS |
| Audio codec | Realtek ALC663 |
| Audio features | High Definition audio, 5.1 surround sound |
| **I/O controller on board** | |
| Serial ATA total | 4 |
| Controller functions | Serial ATA II<br>3 GBit |
| **Interfaces** | |
| Audio: line-in | 1 |
| Audio: line-in / microphone | 1 |
| Audio: line-out | 1 |
| Front audio: microphone | 1 |
| Front audio: headphone | 1 |
| USB 2.0 total | 8 |
| USB front | 2 |
| USB rear | 4 |
| USB internal | 2 |
| VGA | 1 |
| DisplayPort | 1 (optional) |
| DVI | 1 (optional) |
| Serial (RS-232) | 1 (9pin, 16 byte FIFO, 16550 compatible) |
| Mouse / Keyboard (PS/2) | 2 |
| Ethernet (RJ-45) | 1 |
| Parallel | 1 (optional) (25pin with EPP and ECP) |
| Interface Module notes | Anytime USB charge functionality |
| **Input device / components** | |
| | Optical USB wheel mouse<br>Keyboard |
| **Drive bays** | |
| Drive bays total | 5 |
| 3.5-inch internal bays | 2 |
| 3.5-inch external bays | 1 |
| 5.25-inch external bays | 2 |

| | |
|---|---|
| **Slots** | |
| PCI-Express x16 | 1 x (210 mm) Full height |
| PCI-Express x1 | 1 Full height |
| PCI (32-bit / 33 MHz) | 2 x (170/ 220 mm) Full height |
| **Graphics on board** | |
| Graphics brand name | Intel® GMA 4500 |
| Shared video memory | up to 1759 MB |
| Refresh rate 1024 x 768 (recommended / max.) | 85 Hz / - |
| Refresh rate 1280 x 1024 (recommended / max.) | 85 Hz / - |
| Refresh rate 1600 x 1200 (recommended / max.) | 85 Hz / - |
| TFT resolution (VGA) | 1360 x 768 pixel<br>1440 x 900 pixel<br>1600 x 900 pixel<br>1680 x 1050 pixel<br>1920 x 1080 pixel<br>1920 x 1200 pixel |
| Graphics features | DirectX 10<br>HDCP support<br>OpenGL® 2.0 |
| Graphics notes | Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz |
| **Electrical values** | |
| | 0-Watt mode with hard-off switch |
| Power supply input | 200 - 240 V ~1,5A |
| Rated voltage range | 200 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 200 V - 240 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 300 W |
| Monitor outlet | No |
| **Power consumption** | |
| Power consumption note | See white paper Energy Consumption |
| Link to Energy White Paper | http://docs.ts.fujitsu.com/dl.aspx?id=2a51d0d3-000c-47a3-ae8a-19c00547e984 |
| **Heat dissipation** | |
| Heat dissipation notes | See white paper Energy Consumption |
| **Noise for standard configuration (HDD, ODD, FDD)** | |
| Noise emission | According to ISO9296 |
| Related Processors for noise | Intel® Core™2 Quad Q8300 |
| Noise Operation mode 1: ODD load (Blue angel requirement) | 5.1 B / 36 dB(A) |
| Noise Operation mode 2: HDD load (Blue angel requirement) | 4.5 B / 30 dB(A) |
| Noise Operation mode 3: CPU 90% load (Blue angel requirement) | 5.1 B / 36 dB(A) |
| Noise Operation mode 4: High load | 5.2 B / 37 dB(A) |
| Noise Operation mode 5: Office applications | 4.7 B / 32 dB(A) |
| Idle mode (Blue Angel requirement) | 4.4 B / 29 dB(A) |

| | |
|---|---|
| **Noise for standard configuration (HDD, ODD, FDD)** | |
| **Noise notes / description** | A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position |
| **Dimensions / Weight / Environmental** | |
| **Dimensions (W x D x H)** | 175 x 425 x 353 mm |
| **Operating position** | Vertical |
| **Weight** | approx. 11 kg |
| **Weight notes** | Actual weight may vary depending on configuration |
| **Operating ambient temperature** | 15 - 35°C |
| **Compliance** | |
| **Product** | ESPRIMO P2560 |
| **Model** | MI4W-D3041 |
| **Europe** | CE |
| **Global** | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL) |
| **Compliance link** | https://sp.ts.fujitsu.com/sites/certificates/default.aspx |
| **Additional Software** | |
| **Additional software (preinstalled)** | Nero Essentials S (burning software) |
| **Additional software (optional)** | Drivers & Utilities DVD (DUDVD)<br>Recovery DVD for Windows®<br>Nero 9 Essentials XL |
| **Compatibility (references)** | |
| | DMI 2.0<br>PC 2001<br>WMI 1.5<br>USB 2.0<br>SMBIOS |
| **Manageability** | |
| **Manageability technology** | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode) |
| **DeskView components** | WoL (Wake on LAN) |
| **Security** | |
| **System protection** | Kensington Lock support<br>Eye for padlock |
| **Audit proof protection** | Boot sector virus protection<br>Control of external interfaces |
| **Access protection** | User and supervisor BIOS password<br>Optional: Access protection via external SmartCard reader |
| **Packaging information** | |
| **Packaging dimension** | 500x290x540 mm |
| **Max. quantity / pallet** | 24 |
| **Material - Weight (g) Carton** | 1270 g |
| **Material - Weight (g) EPS / PS** | 210 g |
| **Material - Weight (g) PE** | appr. 60 g |
| **Packaging notes** | printed user documentation is bleached in chlorine free process |
| **Warranty** | |
| **Service level** | (depending on country) |
| **Maintenance and Support Services - the perfect extension** | |
| **Recommended Service** | 5x9, Response Time: Next Business Day |
| **Spare Parts availability** | 3 years |

## Warranty

| | |
|---|---|
| **Service Weblink** | http://ts.fujitsu.com/Supportservice |

# More information

## Fujitsu platform solutions

In addition to Fujitsu ESPRIMO P2560, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

**Dynamic Infrastructures**
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

**Computing Products**
www.fujitsu.com/global/services/computing/

**Software**
www.fujitsu.com/software/

## More information

Learn more about Fujitsu ESPRIMO P2560, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com/ESPRIMO

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/

## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2011-07-29 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions